



## AnyLynx™ 5001

Data communication anytime and anywhere: with AnyLynx you can easily and safely expand your IT-network and integrate distant locations or mobile devices in the local network.

With the AnyLynx product family AnyWeb offers a flexible data communication solution for mobile or fixed outdoor installations. The box withstands temperature extremes and vibrations and is ruggedly designed.

### **AnyLynx™ 5000 Series – compact and complete**

The main feature of the AnyLynx 5000 Series is the compact design. Due to the intelligent design of AnyLynx 5000 functionality can easily be expanded or limited. E.g. the number of WLAN Access Points or Bridges or the kind of fixed network ports (Ethernet, ADSL) can vary. This offers a solution which fits perfectly in existing conditions and which can easily be custom-tailored.

## AnyLynx™ 5001

AnyLynx 5001 offers the possibility to install the connectors (AnyConnect) separated from the system box with the Router and Switch. The connector box (AnyConnect) and the system box (AnyStack) are two separate components which are connected with a flexible cable. AnyLynx 5001 is ideal for the assembly in existing chassis. The system box is equipped with an active air ventilation system.

AnyStack offers the following components:

- Cisco 3200 Rugged Integrated Services Router
- Cisco IOS
- Cisco Fast Ethernet Switch
- WLAN 802.11b/g and 3G
- Antenna Terminal 3G and WLAN

AnyConnect integrates three Fast Ethernet ports and the ports for power supply and data.

The deployments of the AnyLynx 5000 Series are as numerous as the requirements of mobile IT networks. Possible deployments for AnyLynx 5000 Series are mobile ticketing machines, gauging stations, surveillance systems, temporary WLAN hotspots, information corners or other mobile installations.

### Technical Data AnyLynx™ 5001

	AnyLynx 5001
<b>Communication Interface</b>	
ADSL	–
Cisco WLAN 802.11b/g (Access Point or Bridge)	●
3G (GPRS, EDGE, UMTS, HSPA)	●
Cablynx (Sierra MC878x Modem)	●
<b>Cisco Router</b>	
IOS Advanced Enterprise	●
<b>Ethernet Switch</b>	
Number of Ports	3
VLAN/Trunk	3
<b>Assembly</b>	
Management (Data Link)	RJ45
Antenna terminals (WLAN/3G)	Facra
Ethernet	RJ45
Dimensions AnyConnect	17x10x5 cm
Dimensions AnyStack	16x16x10 cm
Net weight AnyConnect	0.6 kg
Net Weight AnyStack	2.6 kg
Net Weight incl. Hull	3.9 kg
<b>Operation Temperature</b>	–20 to +60°C
<b>Power Supply</b>	
DC	9–24 Volts
AC (External Adapter)	110–240 Volts
<b>Cisco Compatible*</b>	●

\* AnyLynx has tested compatible with the Cisco 3200 Series Wireless and Mobile Router. The Cisco Compatible logo signifies that AnyLynx has undergone interoperability testing by AnyWeb together with Cisco and a third-party test house based on testing criteria set by Cisco. AnyWeb is solely responsible for the support and warranty of its product. Cisco makes no warranties, express or implied, with respect to AnyWeb product or its interoperation with the listed Cisco product(s) and disclaims any implied warranties of merchantability, fitness for a particular use or against infringement.